







BS-250HAS / 300HAS / 400HAS / 450HAS



BS-250HAS.GA/BS-300HAS.GA

BS Series Automatic Pivot Bandsaws Machine



A THU

Mod

BS

BS

В





PNC+ Inverter + Amplifying Valve



PNC Control Panel







lei item	Unit	Α	В	С	D	E	F	G
-250HAS	mm	1653	1550	2190	593	740	1772	1956
	inch	65.08	61.02	86.22	23.35	29.13	69.76	77.01
-300HAS	mm	1761	1550	2199	593	740	1772	1956
	inch	69.33	61.02	86.57	23.35	29.13	69.76	77.01
-400HAS	mm	2087	1812	2024	642	777	1890	2207
	inch	82.17	71.34	79.69	25.28	30.59	74.41	86.89
-450HAS	mm	2305	2033	2676	704.5	868	2018	2251
	inch	90.75	80.04	105.35	27.74	34.17	79.45	88.62





1 PNC Control Panel

- **OCutting Piece Counter**
- **©Blade Speed LED-Display**
- OMultiple Stroke Feed Counter
- 2 Inverter Control (Optional)

Easily Operate The Control Of The Cutting Speed.

Amplifying Valve (Optional)

Control The Pressure And Flow Rate Of The Cutting Material.



- **OTwo-Way Cylinder**
- **The Digital Cut Length Counter**

Optional Accessories

- 1. Automatic Chip Conveyor
- 2. Variable Blade-Speed Drive
- 3. Variable Vise Pressure System
- 4.Amplifying Valve For Auto-Adjusting Cutting Feed-Rate
- Additional Spare Roller Table, Wire Brush, Saw Blade, Work-area Light, etc.
- 6.GA NC Control



BS-400HAS.GA/BS-450HAS.GA

BS Series Automatic Pivot Bandsaws Machine



		Specific	ations of BS	Model					
Item	Unit	BS-250HAS	BS-300HAS	BS-400HAS	BS-450HAS				
Cutting Capacity	mm	●260 ■300W x 180H ■280W x 250H	●330 ■350W x 250H ■300W x 300H	●400 ■400W x 320H	●460 ■460W x 407H				
	inch	●10 ■12W x 7H ■11W x 10H	●13 ■13W x 10H ■12W x 12H	●16 ■16W x 12H	●18 ■18W x 16H				
Bundle Cutting	mm	200W x 140H	250W x 165H	320W x 205H	360W x 255H				
	inch	8 W x 5 1/2H	10W x 6 1/2H	13" W x 8"H	14W x 10H				
Blade Size	mm	32 x 1.1 x 3660	32 x 1.1 x 3820	32 x 1.1 x 4115	38 x 1.3 x 4880				
	inch	1 1/4 x 0.042 x 144	1 1/4 x 0.042 x 150	1 1/4 x 0.042 x 162	1 1/2 x 0.05 x 192				
Motor Output	HP	Blade-3 HYD-1 Coolant- 1/8	Blade-5 HYD-1 Coolant- 1/8	Blade-5 HYD-1 Coolant- 1/8	Blade-7.5 HYD-2 Coolant- 1/8				
biade	M/Min	25 , 32, 42, 55, 70, 80 Variable Speed 20-80 OPT.							
	F/Min	82, 105, 138, 180, 230, 260 Variable Speed 65-260 OPT.							
Shipping Volume	mm	2120Lx2090W x1500H	2120Lx2090W x1600H	2150Lx2240W x1770H	2540Lx2270W x1920H				
	inch	83.5Lx82.3W x59H	83.5Lx82.3W x63H	84.6Lx88.2W x69.7H	100Lx89.4W x75.6H				
Weight Net/Gross	Kg	1380 / 1610	1410 / 1640	1630 / 1950	3100 / 3500				
	ℓb	3036 / 3542	3102 / 3608	3586 / 4290	6820 / 7700				

The manufacturer reserves the right to modify the design, specifications or mechanisms, to improve the performances, without prior notice. All the specifications shown here are for reference only.

Standard Accessories Of BS Series

- © 7 ft.(2M) Long Roller Table ··········· 1 se
- O Band-Cleaning Wire Brush ······1 piece
- Band saw Blade piece
- Instruction Manual······1 copy



www.bandsaw.com.tw

MEGA MACHINE CO., LTD.

Address: No. 180, Industrial Road, Tai-Ping City, 41154 Taichung, Taiwan, R.O.C. TEL: 886-4-2271 2877(PRES.) FAX: 886-4-2271 5016

E-Mail:mega@ms1.hinet.net

BS - XXX HAS XXX - C

BS - Automatic Pivot Bandsaws

- XXX - Capacity of Product

HAS - Properties of Product

(HAS:Vise Rack Feed / AF:Vise Full Stroke Feed / HAF:Front Vise Full Stroke Feed, Rear Vise Rack Feed)

Please inform our company to get the details.