VERTICAL VARIABLE
SPEED BANDSAW WITH
AUTO-SLIDING TABLE



T-JAW MACHINERY WORKS CO., LTD.



#### SPECIFICATIONS

Height Under Guide

Throat, Band to Column

Blade Speed

Blade Width

Blade Length

Size of Table

Tilt, Main Table

Motor
No. of "T" Slots in Table
Table Stroke

Table Feed Operation Machine Size

Net Weight

Ship Weight

Packing Size

165mm

6-1/2" 360mm

14-1/8\* 25-117m/mln

82-384ft/min 3-13mm 1/8"-1/2"

3025mm 119-1/8" 565 x 500mm

565 x 500mm 22-1/4" x 19-5/8" 5" R, 5" L

1HP None 235mm

235mm 9-1/4"

Electric Powered 930 x 950 x 1710mm 36-5/8" x 37-3/8" x 67-1/4"

350 kgs 770 lbs

430 kgs 946 lbs

1030 x 700 x 1900mm 40-1/2" x 27-1/2" x 74-3/4"

MODEL 360D

#### STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, rip fence, infinitely variable speed, rubber bonded saw wheels, magnetic switches and electric powered table.

OPTIONAL ACCESSORIES: 110 Volt Control & Lighting

#### SPECIFICATIONS

Height Under Guide

Throat, Band to Column

Blade Speed

Blade Width

Blade Length

Size of Table

Tilt, Main Table Motor

No. of "T" Slots in Table Table Stroke

Table Feed Operation Machine Size

Net Weight

Ship Weight

**Packing Size** 

215mm

8-1/2" 400mm

15-3/4" 20-376m/min

65-1233ft/min

3-15mm

3-15mm 1/8"-5/8"

3300mm

129-7/8"

600 x 560mm

23-5/8" x 22"

5' R, 5' L

2HP

260mm

10-1/4"

Electric Powered

1015 x 1040 x 1880mm 40" x 40-7/8" x 74"

580 kgs

1276 lbs

670 kgs

1474 lbs

1010 x 910 x 2000mm 39-3/4" x 35-7/8" x 78-3/4"

MODEL 400D



Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, rip fence, 4 "T" slots in table, Infinitely variable speed, rubber bonded saw wheels, magnetic switches, electric powered table, 110 volt control & lighting.

OPTIONAL ACCESSORIES:

Work Holding Jaw

Circle Cutting Attachment

Miter Gauge





#### SPECIFICATIONS

Height Under Guide

Throat, Band to Column

Blade Speed

**8lade Width** 

Blade Length

Size of Table

Table Stroke

Tilt, Main Table No. of "T" Slots in Table

Table Feed Operation Machine Size

Net Weight

Ship Weight

Packing Size

215mm

8-1/2"

450mm 18"

25-117m/mln

82-384ft/min

3-15mm

1/8"-5/8" 3570mm

140-1/2"

565 x 500mm

22-1/4" x 19-5/8" 5' R, 5' L

1HP

None

235mm

9-1/4"

Electric Powered 1030 x 950 x 1870mm

40-1/2" x 37-3/8" x 73-5/8" 410 kgs

902 lbs

490 kgs

1078 lbs

1130 x 700 x 2050mm 44-1/2" x 27-1/2" x 80-3/4"

## MODEL 450D

#### STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, rip fence, infinitely variable speed, rubber bonded saw wheels, magnetic switches and electric powered table.

OPTIONAL ACCESSORIES:

110 Volt Control & Lighting

#### SPECIFICATIONS

Height Under Gulde

Throat, Band to Column

Blade Speed

Blade Width

Blade Length

Size of Table

Tilt, Main Table Motor

No. of "T" Slots in Table Table Stroke

Table Feed Operation Machine Size

Net Weight

Ship Weight

Packing Size

330mm 12-7/8"

510mm

20"

25-456m/min 82-1496ft/min

3-25mm

1/8"-1" 4070mm

180-1/4"

740 x 680mm

29-1/8" x 26-3/4"

5' R, 5' L

2HP

320mm

12-1/2"

Electric Powered

1210 x 1180 x 2050mm

47-3/8" x 46-3/8" x 80-3/4"

630 kgs 1386 lbs

730 kgs

1606 lbs

1130 x 960 x 2220mm

44-1/2" x 37-3/4° x 87-3/8"

# MODEL 500D

#### STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guldes, chip blower, cleaning brush, rip fence, 4 "T" slots in table, infinitely variable speed, rubber bonded saw wheels, magnetic switches, electric powered table,

110 volt control & lighting. OPTIONAL ACCESSORIES:

Work Holding Jaw Circle Cutting Attachment

Miter Gauge





#### SPECIFICATIONS

Height Under Guide

Throat, Band to Column

Blade Speed

Blade Width

Blade Length

Size of Table

Tilt, Main Table Motor

No. of "T" Slots in Table Table Stroke

Table Feed Operation Machine Size

Net Weight

Ship Weight

Packing Size

274mm 10-3/4"

600mm

25-456m/min 82-1496fvmin

3-25mm 1/8"-1"

4376mm 172-1/4"

740 x 680mm 29-1/8" x 26-3/4"

5'R. 5'L 2HP

320mm 12-1/2

Electric Powered 1300 x 1170 x 2060mm 51-1/8" x 46" x 81-1/8"

700 kgs 1540 lbs

800 kgs 1760 lbs

1390 x 880 x 2250mm 54-3/4" x 34-5/8" x 89"

## MODEL 600D

#### STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush. rip fence, 4 "T" slots in table, infinitely variable speed, rubber bonded saw wheels. magnetic switches, electric powered table, 110 volt control & lighting. OPTIONAL ACCESSORIES:

Work Holding Jaw Circle Cutting Attachment Miter Gauge

### SPECIFICATIONS

Height Under Guide

Throat, Band to Column

Blade Speed

Blade Width

Blade Length

Size of Table

Tilt, Main Table

No. of "T" Slots in Table Table Stroke

Table Feed Operation Machine Size

Net Weight

Ship Weight

Packing Size

325mm 12-5/B" 715mm 28-1/8" 20-394m/min 65-1292ft/min

3-25mm 1/8"-1"

4090mm 161"

740 x 680mm 29-1/8" x 26-3/4" 5' R, 5' L

2HP

Electric Powered

1420 x 1200 x 2040mm 55-7/8" x 47-1/4" x 80-3/8"

730 kgs 1606 lbs

830 kgs 1826 lbs

1340 x 880 x 2090mm

# MODEL 700D

#### STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, rip fence, 4 "T" slots in table, infinitely variable speed, rubber bonded saw wheels, magnetic switches, electric powered table. 110 volt control & lighting.

### OPTIONAL ACCESSORIES:

Work Holding Jaw Circle Cutting Attachment Miter Gauge





## VERTICAL VARIABLE SPEED BANDSAW WITH AUTO-SLIDING TABLE

#### SPECIFICATIONS

Height Under Guide

Throat, Band to Column

Blade Speed

Blade Width

Blade Length

Size of Main Table

Size of Auxillary Table

Tift, Main Table Motor

No. of "T" Slots in Table Table Stroke, Main Table

> Table Feed Operation Machine Size

> > Net Weight

Ship Weight

Packing Size

325mm 12-5/8

1010mm

39-3/4"

20-394m/min 65-1292ft/min

3-25mm

1/8"-1"

4670mm 183-7/8"

740 x 680mm

29-1/8" x 26-3/4" 679 x 477mm

26-3/4" x 18-3/4"

5 R. 5 L

2HP

320mm

12-1/2"

Electric Powered

1690 x 1210 x 2040mm

66-1/2" x 47-5/8" x 80-3/8"

810 kgs

1782 lbs 910 kgs

2002 lbs

1690 x 1030 x 2100mm 66-1/2" x 40-1/2" x 82-5/8"

MODEL 1000D

STANDARD FEATURES/ACCESSORIES:

Blade welder, shear, grinder, work light, blade guides, chip blower, cleaning brush, rip fence, 4 "T" slots in table, infinitely variable speed, rubber bonded saw wheels, magnetic switches, electric powered table, 110 volt control & lighting.


OPTIONAL ACCESSORIES:

Work Holding Jaw

Circle Cutting Attachment

Miter Gauge

## T-JAW OPTIONAL ACCESSORIES



Circle Cutting Attachment



Miter Gauge



Work Holding Jaw

#### STANDARD MACHINE FEATURES:

- · Infinitely variable speed.
- The band tension is cushioned.
- Blade welder and grinder are front mounted for quick, accurate blade repair and installation.
- · Interchangeable rubber bonded saw wheels.
- · Brush for cleaning lower drive wheel.
- Maintenance-free airpump provides air to remove chips from the point of cut.
- · The upper wheel could be adjusted for band tensioning.
- · Hand wheel controlled speed.
- · Adjustable saw blade guides.
- · Machine light is fitted.
- Change speeds while the machine is in operation, without stopping, without pulley changes.
- · Cast iron frame to minimize machine vibration.
- The machine is with a device for automatic linear cutting.
- · Work table may take speedy reverse movement.
- Moton of work table is controlled by stepless speed controller.
- · Work table is with auto stoppers.



E-mail: bandsaw@ms15.hinet.net